











Figure similar

Analog monitoring relay Phase failure and sequence 3 x 160...690 V 50...60 Hz AC 2 change-over contacts screw terminal Successor product for 3UG3513-1BL50 or 3UG3513-1PB50

product brand name	SIRIUS
product designation	Network monitoring relay with analog setting
design of the product	2 functions
product type designation	3UG4
General technical data	
product function	Phase monitoring relay
display version LED	Yes
insulation voltage for overvoltage category III according to IEC 60664	690 V
• with degree of pollution 3 rated value	
degree of pollution	3
type of voltage	AC
• for monitoring	
• of the control supply voltage	AC
surge voltage resistance rated value	6 kV
protection class IP	IP20
shock resistance acc. to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
vibration resistance acc. to IEC 60068-2-6	1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical	100 000
thermal current of the switching element with contacts maximum	5 A
reference code acc. to IEC 81346-2	K
relative repeat accuracy	1 %
Substance Prohibitance (Date)	28.05.2009 00:00:00
Product Function	
product function	
• undervoltage detection	No
• overvoltage detection	No
• phase sequence recognition	Yes
• phase failure detection	Yes
• asymmetry detection	No
• overvoltage detection 3 phase	No
• undervoltage detection 3 phases	No
• voltage window recognition 3 phase	No
• adjustable open/closed-circuit current principle	No

<ul style="list-style-type: none"> • auto-RESET 	Yes
Control circuit/ Control	
control supply voltage at AC	
<ul style="list-style-type: none"> • at 50 Hz rated value • at 60 Hz rated value 	160 ... 690 V 160 ... 690 V
operating range factor control supply voltage rated value at AC at 50 Hz	
<ul style="list-style-type: none"> • initial value • full-scale value 	1 1
operating range factor control supply voltage rated value at AC at 60 Hz	
<ul style="list-style-type: none"> • initial value • full-scale value 	1 1
Auxiliary circuit	
number of NC contacts delayed switching	0
number of NO contacts delayed switching	0
number of CO contacts delayed switching	2
operating frequency with 3RT2 contactor maximum	5 000 1/h
Main circuit	
number of poles for main current circuit	3
Outputs	
ampacity of the output relay at AC-15	
<ul style="list-style-type: none"> • at 250 V at 50/60 Hz • at 400 V at 50/60 Hz 	3 A 3 A
ampacity of the output relay at DC-13	
<ul style="list-style-type: none"> • at 24 V • at 125 V • at 250 V 	1 A 0.2 A 0.1 A
operational current at 17 V minimum	5 mA
continuous current of the DIAZED fuse link of the output relay	4 A
Electromagnetic compatibility	
conducted interference	
<ul style="list-style-type: none"> • due to burst acc. to IEC 61000-4-4 • due to conductor-earth surge acc. to IEC 61000-4-5 • due to conductor-conductor surge acc. to IEC 61000-4-5 	2 kV 2 kV 1 kV
field-based interference acc. to IEC 61000-4-3	10 V/m
electrostatic discharge acc. to IEC 61000-4-2	6 kV contact discharge / 8 kV air discharge
Galvanic isolation	
galvanic isolation	
<ul style="list-style-type: none"> • between input and output • between the outputs • between the voltage supply and other circuits 	Yes Yes Yes
Connections/ Terminals	
product function removable terminal for auxiliary and control circuit	Yes
type of electrical connection	screw-type terminals
type of connectable conductor cross-sections	
<ul style="list-style-type: none"> • solid • finely stranded with core end processing • at AWG cables solid • at AWG cables stranded 	1x (0.5 ... 4 mm ²), 2x (0.5 ... 2.5 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.5 mm ²) 2x (20 ... 14) 2x (20 ... 14)
connectable conductor cross-section	
<ul style="list-style-type: none"> • solid • finely stranded with core end processing 	0.5 ... 4 mm ² 0.5 ... 2.5 mm ²
AWG number as coded connectable conductor cross section	
<ul style="list-style-type: none"> • solid 	20 ... 14

• stranded	20 ... 14		
tightening torque with screw-type terminals	0.8 ... 1.2 N·m		
Installation/ mounting/ dimensions			
mounting position	any		
fastening method	snap-on mounting		
height	92 mm		
width	22.5 mm		
depth	91 mm		
required spacing			
• with side-by-side mounting			
— forwards	0 mm		
— backwards	0 mm		
— upwards	0 mm		
— downwards	0 mm		
— at the side	0 mm		
• for grounded parts			
— forwards	0 mm		
— backwards	0 mm		
— upwards	0 mm		
— at the side	0 mm		
— downwards	0 mm		
• for live parts			
— forwards	0 mm		
— backwards	0 mm		
— upwards	0 mm		
— downwards	0 mm		
— at the side	0 mm		
Ambient conditions			
installation altitude at height above sea level maximum	2 000 m		
ambient temperature			
• during operation	-25 ... +60 °C		
• during storage	-40 ... +85 °C		
• during transport	-40 ... +85 °C		
Certificates/ approvals			
General Product Approval	EMC	Declaration of Conformity	Test Certificates
 CCC	 UL	 RCM	 EG-Konf.
		Miscellaneous	Type Test Certificates/Test Report
Test Certificates	Marine / Shipping	other	Railway
Special Test Certificate	 LRS	 DNV-GL	Confirmation Vibration and Shock
Further information			
Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10			
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UG4512-1BR20			
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UG4512-1BR20			
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3UG4512-1BR20			
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)			



last modified:

12/21/2020 