



Figure similar

SIMATIC S7-1200, Digital I/O SM 1223, 8 DI/8 DO, 8 DI 24 V DC, Sink/Source, 8 DO, transistor 0.5 A

General information	
Product type designation	SM 1223, DI 8x24 V DC, DQ 8x24 V DC
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	145 mA
Digital inputs	
• from load voltage L+ (without load), max.	4 mA; per channel
output voltage / header	
supply voltage of the transmitters / header	
• product function / supply voltage for transmitters	Yes
Power loss	
Power loss, typ.	2.5 W
Digital inputs	
Number of digital inputs	8
• in groups of	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8
horizontal installation	
— up to 40 °C, max.	8
— up to 50 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	5 V DC at 1 mA
• for signal "1"	15 V DC at 2.5 mA
Input current	
• for signal "0", max. (permissible quiescent current)	1 mA
• for signal "1", min.	2.5 mA
• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in

	groups of four
for interrupt inputs	
— parameterizable	Yes
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	300 m
<b>Digital outputs</b>	
Number of digital outputs	8
• in groups of	1
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	L+ (-48 V)
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
<b>Output voltage</b>	
• Rated value (DC)	24 V
• for signal "0", max.	0.1 V; with 10 kOhm load
• for signal "1", min.	20 V DC
<b>Output current</b>	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, max.	0.5 A
• for signal "0" residual current, max.	10 µA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	50 µs
• "1" to "0", max.	200 µs
<b>Total current of the outputs (per group)</b>	
horizontal installation	
— up to 50 °C, max.	4 A; Current per mass
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnostics indication LED</b>	
• for status of the inputs	Yes
• for status of the outputs	Yes
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
• between the channels, in groups of	2
<b>Potential separation digital outputs</b>	
• between the channels, in groups of	1
• between the channels and backplane bus	500 V AC
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
<b>Ambient conditions</b>	
<b>Free fall</b>	
• Fall height, max.	0.3 m; five times, in product package
<b>Ambient temperature during operation</b>	
• min.	-20 °C
• max.	60 °C

• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
• permissible temperature change	5°C to 55°C, 3°C / minute
<b>Ambient temperature during storage/transportation</b>	
• min.	-40 °C
• max.	70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
<b>Relative humidity</b>	
• Operation at 25 °C without condensation, max.	95 %
<b>connection method</b>	
required front connector	Yes
<b>Mechanics/material</b>	
Enclosure material (front)	
• Plastic	Yes
<b>Dimensions</b>	
Width	45 mm
Height	100 mm
Depth	75 mm
<b>Weights</b>	
Weight, approx.	210 g
<b>last modified:</b>	4/1/2022 